

4ST CAM LOBES APPLICATION CHART '05

	CAM LOBES DISTANCE BETWEEN CENTERS IN MM. (+/- 0.6 MM.)	2005 STD. (IN/EX)	2005 OPT. 1 (IN/EX)	2005 OPT. 2 (IN/EX)
250 MX	IN 34 / EX 31	F1 / F1	N/A	N/A
250 END	IN 34 / EX 31	F1 / F1	N/A	N/A
250 SMR/SMM	IN 34 / EX 31	F1 / F1	N/A	N/A
450 MX	IN 43 / EX 38	F1 / F1	N1 / N2 (SMOOTHER)	N/A
450 SMX	IN 43 / EX 38	C1 / C4	N1 / N2 (SMOOTHER)	N/A
450 END	IN 43 / EX 38	N2 / N3	N1 / N2 (STRONGER)	N/A
450 SMR/SMM	IN 43 / EX 38	N2 / N3	N1 / N2 (STRONGER)	N/A
530 MX	IN 43 / EX 38	F1 / F1	N1 / N2 (SMOOTHER)	N/A
530 END	IN 43 / EX 38	N2 / N3	N1 / N2 (STRONGER)	N/A
530 SMR/SMM	IN 43 / EX 38	N2 / N3	N1 / N2 (STRONGER)	N/A
660 SMX	IN 45.5 / EX 40	N1 / N2	N2 / N3 (SMOOTHER)	F1 / F1 (STRONGER)